Inventory CLOSEOUT

Federated Auto Parts PROFESSIONALS®

Offers Good While Supplies Last!

10-Ton Hydraulic Porto-Power Pump

SFA # B65188

$149.99

1 AVAIL.

'SAVE PHACE' Welding Helmet

- Large viewing area of over 40 sq/in
- 180° auto darkening
- MIG / TIG / MAG / Plasma
- Rotary knob adjusts sensitivity

SFA # 3011681

$179.99

1 AVAIL.

4 AVAIL.

Wheel Arm™ Bars ~ 1 Pair

For use with most two and four posts lifts. These adjustable bars are designed to clamp over the arm of the lift providing a safe and secure place to store the tire and wheel assembly. This helps eliminate tripping hazards and also aids in the prevention of back injuries from lifting large heavy wheels and tires off the ground.

SFA # 92100

- *Adjusts Vertically*
- *Adjusts Horizontally*
- *Ball Joint Arm Socket*

$89.99

2 AVAIL.

$89.99

3-Ton Steel Jack Stands

- Ratcheting action adjustment
- 12" min ~ 19" max height

SFA # HW93503

1 AVAIL.

$439.99

3-Ton Heavy Duty Steel Service Jack

- Designed for the professional with repairability
- Pressure relief valve
- 5" min ~ 23-1/2" max height

SFA # HW93652

HOOK SUSPENDED HAND CHAIN HOISTS

BUDGIT®

1 EA. AVAILABLE

• Combining ease of use with exceptional strength and reliability. The rugged cast aluminum alloy casting frame is strong enough for heavy use, yet light weight for easy portability. A unique "gag-resistant" hand chain wheel cover guides the chain and ensures smooth, efficient operation. Standard overload protection device and Weston type load brakes ensure accurate load control.

• Designed for portable "Use Anywhere" type service. Rugged design provides long life in industrial and construction service and is frequently used for rigging and off-vertical lifting applications.

Capacity	Lift	Headroom	Weight	Hoist Number	CLOSEOUT
1-TON	8 ft	13-1/4"	44 lbs	DRS # 8262	$399.99
2-TON	8 ft	16-1/4"	57 lbs	DRS # 8263	$499.99

$59.99

5 AVAIL.

EVA Foam Pad w/ 21-LED light Strip

SFA # 85001

1 AVAIL.

$49.99

Mechanic's Toolbox Seat

- 450 Lbs. rated capacity
- Steel frame construction
- Extra thick seat cushion
- 3 drawer toolbox with front and back tool trays
- 3" oil resistant, full bearing casters

SFA # 92450

REELCRAFT®

PTO # TA-50-SA-S

Saddle Mount 50 Gal. Hydraulic Aluminum Tank

Has machined ports and comes with all mounting hardware and brackets.

$269.99

1 AVAILABLE

AMPROBE®

INVENTORY CLOSEOUT!

WHILE SUPPLIES LAST

AMP # TMD90A

1 AVAILABLE

$89.99

Dual-Input Digital Thermometer with Triple Display

Dual-input thermometer offers a wide temp range and accepts type K, J, T, R, S, E thermocouplers and is ideal for HVAC/R technicians and electricians.

- High accuracy, multiple type input thermometer
- Displays T1, T2, and T1-T2 simultaneously
- Dual inputs for easy Super-Heat & Sub-Cool
- Accepts six different thermocouple types
- Outputs real time measurement data with time stamp
- Measures from -328°F / -200°C to 3200°F / 1760°C
- Deluxe carrying case and two Type K probes
- Built-in RS-232 port for downloading to PC

COUPLER	RANGE	BEST ACCURACY
Type K	-328 °F - 2498 °F (-200 °C - 1370 °C)	0.1 % rdg + 1.4 °F (0.1 % rdg + 0.7 °C)
Type J	-328 °F - 1400 °F (-200 °C - 760 °C)	0.1 % rdg + 1.4 °F (0.1 % rdg + 0.7 °C)
Type T	-328 °F - 730 °F (-200 °C - 390 °C)	0.1 % rdg + 1.4 °F (0.1 % rdg + 0.7 °C)
Type R S	32 °F - 3200 °F (0 °C - 1760 °C)	0.1 % rdg + 1.4 °F (0.3 % rdg + 0.7 °C)
Type E	-328 °F - 1832 °F (-200 °C - 736 °C)	0.1 % rdg + 1.4 °F (0.3 % rdg + 0.7 °C)

OPERATING CONDITIONS: 0 °C to 50 °C (32 °F to 122 °F) at 0 to 85 % R.H. (non-condensing)

AMBIENT COEFFICIENT: 0 °C to 18 °C and 28 °F to 50 °C (ambient temperatures) for each °C ambient below 18 °C or above 28 °C, add the following tolerance into the accuracy spec: 0.01 % of reading +0.03 °C (0.01 % of reading +0.06 °F)

ACCURACY

AC Current ~ 0 to 350 A

± (1.6% of Rdg + 0.5A)

AC Current ~ 350 to 440 A

± (3.2% of Rdg + 1A)

AMP # A400

1 AVAILABLE

$59.99

Clamp-On Transducer

- For use with multimeters, oscilloscopes, power recorders or any instrument with AC milli-volt input (1 mV AC per Amp)
- AC Current measurement from 0.1 A to 400 A
- Measures 50 or 60 Hz current
- Maximum jaw opening 1.18”
- Accommodates conductors 1.14” in diameter

AMP # MAN02A

2 AVAILABLE

$159.99

Differential Pressure Manometer

The right tool for HVAC/R technicians measuring pressure level, or anyone working with valves, control sensors in a pneumatic control environment. Large dual display shows gauge or pressure values. Shows relative time clock for measuring when events happen, such as minimum and maximum values.

- Measures: In H2O, psi, mbar, bar, mm H2O
- Ideal for measuring HVAC/R pressure levels
- Also used for pneumatic controls
- Min & Max value recording + Data Hold
- Measuring Range: 2 psi (13.8 kPA)
- Accuracy: +/- 0.3 % of full scale at +/- 77 °F (25 °C)
- Response time: 0.5 second
- Sensitivity Resolution: per 0.401 in H2O / 0.001 per 0.0145 psi / 0.1 per mbar
- Built-in RS-232 port for downloading to PC

Pen Probe Digital Multi-Tester

- Unique pen shape for measuring in confined areas
- 600V AC and 600V DC ranges
- Improved DC basic accuracy 0.5%
- Resistance to 34 MΩ
- 3,400-count digital plus analog bargraph
- Continuity beeper
- Two probe tip sizes: 3” & 1/2”
- Cat III 300 V & Cat II 600 V safety rated
- Data Hold to freeze measurement value
- Includes alligator grounding clip

4 AVAILABLE

AMP # DM73C

$49.99